ShenZhen, China

Chenghao/Oem

/

T/T

ROHS ISO9001 CE

CH700WV03A-CTA

7-15 working days

300Kpcs/month

7.0 Inch TFT LCD Capacitive Touchscreen 800*480 Resolution Wide Temperature

Basic Information


- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100 pcs
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- Supply Ability.

Product Specification

- Product Name:
- TFT/CTP Active Area:
- TFT Dot Pitch:
- Interface:
- Operating Temperature:
- Storage Temperature:
- Highlight:
- 7.0 Inch TFT LCD Capacitive Touchscreen154.08(W)×85.92(H)0.1926 (W)×0.1790 (H)24-bit Parallel RGB Interface

All the products are packed in right way to keep it safe. For small sizes of products we use tray + carton, For bigger sizes we use foam slot + carton. we also design packages according to customers' requirements

- -20 ~ +70 °C
- -30~+80 °C
- RoHS compliant LCD Capacitive Touchscreen, Tft Capacitive Touchscreen 7.0 Inch, CH700WV03A-CTA Capacitive Touchscreen



Our Product Introduction

Product Description


7.0 Inch TFT LCD Capacitive Touchscreen 800*480 Resolution Wide Temperature

1. Specification of 800x480 capacitive touchscreen

Display Type	TFT-LCD
Display model	CH700WV03A-CTW
Pixel Configuration	RGB Stripe
Display Resolution	800(RGB)×480
Aspect Ration	0.66
Contrast	500:1 (Typ.) (TM)
Overall Size	180(W)×119(H)×5.27(T) mm
Active Area (A.A)	154.08(W)×85.92(H)
Luminace	280 cd/m ²
Viewing Direction	12 O' clock


2. Description of 800x480 tft touchscreen

- * 7.0 Inch TFT LCD Capacitive Touchscreen 800*480 Resolution Wide Temperature
- * It is composed of a Touch panel, TFT LCD panel, driver IC, FPC, backlight.
- * 7.0-inch color touchscreen display
- * The 7 inch tft touch lcd module is 800(RGB)x480 resolution TFT LCD module, clear display
- * FPC number is 40pin and can be customized, Customized content includes shape structure, interface definition, etc.
- * RoHS & REACH compliant.
- * Using 24-bit Parallel RGB Interface
- * Provide a rich sample program
- * Military-grade process standards, long-term stable work
- * Provide underlying driver technical support
- * Long term stable production and guaranteed supply
- * Backlight with different brightness options from 200 1500cd/m2 are available.
- * Specific touch panel can be designed & customized.
- * Support customized service! Customizable content includes FPC/backlight brightness/installation of touch panel, etc.



3. Quick detail of 800x480 lcd touchscreen


LCM number : CH700WV03A-CTA Resolution : 800× 3(RGB) × 480 Dot pitch : 0.1926 (W)×0.1790 (H) mm Outline dimension : 180(W)×119(H)×5.27(T) mm TFT/CTP Active area : 154.08(W)×85.92(H) mm View angle| : 12:00 Pixel Arrangement : RGB-stripe Surface Treatment : Plant TFT Electrical Interface : 24-bit Parallel RGB Interface Brightness : 280(cd/m2) CTP driver IC : GT911 Contrast ratio : 500



Backlight Type : LED Response time : ******(ms) Display mode : Tn, Normally White, Transmissive Operate temperature : -20-70(°C) Storage temperature : -30-80(°C) Display Colors : 16.7M Backlight lifetime : 20k hrs(Min.) With/without Touch Panel:Without Touch Panel Type:*****

4. Application of wide temp lcd touchscreen

Products are widely used in general communications, household appliances, industrial control, medical equipment, POS machines, instruments, meters, GPS navigation, digital photo frames, netbooks, financial electronics, communication electronics, consumer electronics, information appliances, culture, education, sports and entertainment, etc. field. Such as attendance machine, fingerprint device, access control machine, stock machine, walkie-talkie, video doorbell, learning machine, point reading machine,GPS navigator, and so on .



7th floor, building C5, Hengfeng Industrial City, Hangcheng street, Bao'an District, Shenzhen